

Yellowstone 576 Extra Large, Extra Thick Waterproof Floating Floor



Size
9" Wide - Random Lengths up to 72"
7.5 mm thick

Wear Layer
20 mil / UV-Cured
Enhanced Urethane Protection

Construction
5-Layer WPC

Edge Treatment
Four-Sided Color-Enhanced Bevel

Installation
5G*Fold Down Installation
• Fastest & easiest installation
• Retracting tongue creates the strongest lock
Click Floating Floor
(on, above or below grade)



Attached Cushion
For superior sound abatement and easier installation

Coordinating Moldings
See matrexxfloor.com for more details.

Packaging
5 layers per carton (36 lbs)
22.5 SF per carton
56 cartons per pallet
18 pallets per 20 ft container
23 pallets per 40 ft container

Testing

Critical Radiant Flux	ASTM E648	Class I
Surface Flammability	DOC FF 1-70	Passed
Coefficient of Friction	ASTM 2047	Passed>0.6
Sound Transmission Class (STC)	ASTM E492	64
Impact Insulation Class (IIC)	ASTM E989	73
High Frequency Impact Insulation Class(HIIC)	ASTM E3222	88
Floor Score Certified		
Phthalate Free		
100% Virgin PVC		



Warranties

- Lifetime Waterproof
- Lifetime Residential Wear
- 30-Year Commercial Wear

See full warranty text at matrexxfloor.com

Sample SKUs

Handle Boards
HB576MX
5 per carton

Strap Sets
SS576MX
5 per carton

Step Up Display
8CARDS576MX-1
8CARDS576MX-2
FIXT576MX
Packaged in 3 cartons

