

# Carbonado Plus 561



**Size**  
7" x 48" *nominal* (18 cm x 122 cm)  
5.5 mm thick

**Wear Layer**  
20 mil / UV-Cured Urethane

**Edge Treatment**  
Four-Sided Color-Enhanced Bevel

**Installation**  
Drop Lock, Click Floating Floor  
(on, above or below grade)

**Attached Cushion**  
For superior sound abatement and easier installation

**Coordinating Moldings**  
See [matrexxfloor.com](http://matrexxfloor.com) for more details.

**Packaging**  
10 pieces per carton (40 lbs)  
23.7 SF per carton  
65 cartons per pallet  
20 pallets per container

**Testing**

Critical Radiant Flux	ASTM E648	Class I
Surface Flammability	DOC FF 1-70	Passed
Coefficient of Friction	ASTM 2047	Passes > 0.6
Static Load Limit	ASTM F970	3000 lbs <i>without cushion</i>
Sound Transmission Class (STC)	ASTM E492	65
Impact Isulation Class (IIC)	ASTM E989	72
High Frequency Impact Isulation Class (HIIC)	ASTM E3222	92

Floor Score Certified  
Phthalate Free  
100% Virgin PVC



**Warranties**

- Lifetime Waterproof
- Lifetime Residential Wear
- 20-Year Commercial Wear

See full warranty text at [matrexxfloor.com](http://matrexxfloor.com)

**Sample SKUs**

**Handle Boards**  
HB561MX  
5 per carton (63 lbs)

**Strap Sets**  
SS561MX  
5 per carton (40 lbs)

**Step Up Display**  
8CARDS561MX-1  
8CARDS561MX-2  
FIXT561MX  
Packaged in 3 cartons (125 lbs)